


Activated carbon filter element

Activated carbon is used because of its reducing effect against organic contamination (e.g. contamination from Paint, Odor and Flavor, Chlorine, Pesticide).

Applications:

- Water Purification
- Separation of Chlorine
- Drinking Water
- Separation of Pesticide
- Pharmaceutical Products
- Separation of Organic Materials
- Cosmetics and Food
- Color and odor removal



General Technical Data

Type:	AEM	AEV
Pre-Filter:	Polypropylene (Meltblown)	Polypropylene-Fleece
Activated Carbon Type:	Pressed Activated Carbon	Pressed Activated Carbon
Micron Rating:	5 µm	5 µm
Max. Temp.:	50 °C	82 °C 50 °C for 30"
Outer Diameter:	64 mm	68 mm
Gaskets:	Polyethylene	Buna
Adapter:	DOE	DOE

Order information:

A -

Pre-Filter and type of the activated carbon		Micron Rating		Length	
EM	Polypropylene Meltblown Pressed Activated Carbon	5	5 µm	9	9 3/4"
				10	10"
				20	20"
EV	Polypropylene-Fleece Pressed Activated Carbon	5	5 µm	9	9 3/4"
				10	10"
				20	20"
				30	30"*

*Max. Temp.: 50 °C

Order examples:

AEM5-10

AEV5-20