



AVPP12-N-222 and AVPP20-N-222

The filter housing are used preferred for pre- and fine filtration in the water treatment, electronic and foto industry, as well as in the chemical and surface technology. Filter head und sump are made completly of polypropylene nature. This offers following benefits:

- No fillers, dyes and softening agents
- Good resistance against DI-water and inorganic solvents
- The smooth surface prevents bacteria deposit and bacteria growth

Because filter cartridges with various lengths, ratings and material compositions can be put into the filter, the applications are very wide spread.

General Technical Data

In-/Outlet:	3/4" female thread NPT
Material:	Pure Polypropylene
Seal:	Viton (other Seals available on request)
Working Pressure:	Max. 8 bar at 30 °C
Working Temp..:	Max. 50 °C at 4 bar
Vent:	2 x 1/4" female thread NPT

Filter Cartridges

AVPP12-N-222-C3	1 x 10", Code 3 adapter (222/flat)
AVPP12-N-222-C8	1 x 10", Code 8 adapter (222/fin)
AVPP20-N-222-C3	1 x 20", Code 3 adapter (222/flat)

Measurements

Total Length:	380 mm (AVPP12) 585 mm (AVPP20)
Inside Micrometer between the connections:	130 mm

Order Information:

AVPP -N-222-

Element Length	
12	10"
20	20"

Adapter	
C8	Code 8 (222/Fin)
C3	Code 3 (222/Flat)

Order Example:

AVPP20-N-222-C3